

Stock Range **Chipboard**

1 JANUARY 2026



STOCK RANGE CHIPBOARD

Chipboard non-structural, standard	4
Chipboard non-structural, moisture resistant	6
MDF.RWH, moisture resistant	8
Chipboard non-structural, fire-retardant	10
Chipboard structural, standard	11
Chipboard structural, moisture resistant	13
Chipboard structural, moisture resistant & fire-retardant	17

REACH 2026: what does this mean for you?

In **August 2026**, the new **REACH legislation** comes into force, setting stricter limits on **formaldehyde emissions**. We're ready for the change: from 1 April 2026, for orders placed from that date onwards, our entire stock range will consist of REACH-compliant products only.

To make the transition as smooth as possible for you, you can already see all upcoming changes in this stock list. Until 1 April, you order exactly as you do today, with the existing article codes. Because of our gradual stock transition, you may already receive a REACH-compliant article on the same terms.

In this document, the 'article' column shows what will change for orders placed from 1 April 2026 onwards:

- **The article switches to a REACH-compliant version on 1 April 2026:**
the current article code is listed together with the new code (in orange) and updated name (incl. LF+) that applies from 1 April.
- **The article leaves our stock range after 1 April 2026:**
the current article code shows 'phase out'.
- **A new article enters our range:**
the article code appears in orange, followed by 'new'.

For products that already meet the new requirements today (such as Betonspan, Betonspan Plus and Betonforce Black) and remain in our range after 1 April 2026, nothing changes.

Have a question? Our sales team is happy to help: info.panels@unilin.com.





CHIPBOARD NON-STRUCTURAL, STANDARD

LISO LF+



Standard chipboard P1 for packaging or furniture applications in dry areas.

Topfinish

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
17	55	24676 > 58904	1,90

Sanded

Thickness (mm)	2500x1250 mm			3050x1250 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
16	60	24672 > 58901	1,95	50	24675 > 58902	1,99
18	50	24673 > 58912	1,83	44	10001 > 58909	1,97
22	40	24606 > 58917	1,74			

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes



CHIPBOARD NON-STRUCTURAL, STANDARD

Sanded

BELSPAN LF+



Standard chipboard P2 for furniture and interior finishing in dry areas.

Thickness (mm)	2500x1250 mm			3050x1250 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
8	96	33471 > 58947	1,67	96	33472 > 59368	2,04
10	90	24698 > 59380	2,00	80	9528 > 59385	2,17
12	80	24699 > 59381	2,07	64	9604 > 59386	2,03
15	65	24700 > 58802	2,05			
16	60	24701 > 58803	2,01	50	24706 > 58804	2,05
18	50	24702 > 58805	1,89	44	24707 > 58806	2,03
19	50	24703 > 58846	1,99	40	24708 > 58847	1,95
22	40	24704 > 58849	1,79	36	9822 > 58850	1,97
25				35	24709 > 58851	2,17
28				30	24710 > 58852	2,05
38	20	9879 > 58854	1,48 > 1,55	20	9886 > 58855	1,80 > 1,89

Thickness (mm)	3060x1310 mm			2800x2070 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
8				50	30550 > 44760	1,62
10				50	30551 > 44761	2,03
12				48	37978 > 57636	2,31
16	40 > 36	24662 > 44748	1,72 > 1,54	36	30552 > 44762	2,24 > 2,26
18	33	24663 > 44749	1,60	33	30553 > 44763	2,31 > 2,33
19				30	30554 > 44764	2,23
22				27	30555 > 44765	2,24
25				24	30556 > 44766	2,26
28				21	30557 > 57634	2,19
38				15	9883 > 44767	2,05 > 2,15

Sanded

BELSPAN LF+



Standard chipboard P2 with low formaldehyde emission for furniture and interior finishing in dry areas, compliant with ChemVerbotsV.

Thickness (mm)	3060x1310 mm			2800x2070 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
8				50	44760	1,62
10				50	44761	2,03
12	48	51728 > phase out	1,59			
16	36	44748	1,54	36	44762	2,26
18	33	44749	1,59	33	44763	2,33
19				30	44764	2,23
22				27	44765	2,24
25	24	51729	1,56	24	44766	2,26
38	15	51730 > phase out	1,49	15	44767	2,15



CHIPBOARD NON-STRUCTURAL, MOISTURE RESISTANT

Topfinish

HYDROLIS WRB LF+



Standard chipboard P3 for simple formwork for single use.

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
17	54	24723 > 58893	2,01

Sanded

HYDROLIS LF+



Standard chipboard P3 for furniture and interior finishing in humid areas.

Thickness (mm)	2500x1250 mm			3050x1250 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
10	90	24718 > 58880	2,06			
12	80	24719 > 58881	2,16			
16	60	24720 > 58883	2,10			
18	50	24721 > 58886	1,97	44	6477 > 58888	2,12
22	40	24722 > 58890	1,79			

Sanded

HYDROLIS LF+



Standard chipboard P3 with low formaldehyde emission for furniture and interior finishing in humid areas. Compliant with ChemVerbotsV

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
18	44	51731	2,23



CHIPBOARD NON-STRUCTURAL, MOISTURE RESISTANT

Melamine faced

BETONSPAN



Moisture-resistant chipboard P3 for formwork. Multiple reuse and a smooth concrete surface as result.

Thickness (mm)	2500x1250 mm			3050x1250 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
17	55	134087	2,16	42	131479 > new	1,91

Thickness (mm)	5600x2070 mm		
	#/pack	article	weight/pack
18	12	184125	1,99

Lacquered on 1 side

ACRYSPAN 1S LF+



Moisture-resistant chipboard P3 for reusable formwork.

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
17	54	400011188 > 400109740	2,01

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes



MDF.RWH, MOISTURE RESISTANT

MDF Topfinish

RWH LF+



Vapour-permeable racking board board for wall and roof applications. Ideal for timber frame construction.

Thickness (mm)	2800x1196 mm		
	#/pack	article	weight/pack
16	50	25114 > 58338	1,64

MDF Topfinish

RWH LF+ TG



Vapour-permeable racking board with tongue and groove for quick installations in wall and roof applications. Ideal for timber frame construction.

Thickness (mm)	610x2440 mm			
	#/pack	article	weight/pack	profile
16	100	400022897 > 400109986	1,46	R, TG4*

*TG4: tongue and groove all 4 edges

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes

B25B10
2627

B25B11
7893

4088 2449 15.0
7897

DOMESTIC MEUBLES
4537 2208 15.0
0560

DOMESTIC MEUBLES
4538 2240 15.0
7888



CHIPBOARD NON-STRUCTURAL, FIRE-RETARDANT

Sanded

ANTIVLAM LF+



Flame-retardant chipboard P2 for furniture and interior finishing in dry areas, certified B-s1,d0.

Thickness (mm)	2500x1250 mm			3050x1250 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
10				75	24649 > 58828	2,18
12				64	24651 > 58831	2,20
16				50	24653 > 58834	2,20
18	50	24655 > 58835	2,00	44	24656 > 58836	2,15
22				36	24664 > 58838	2,12

Thickness (mm)	2800x2070 mm		
	#/pack	article	weight/pack
16	30	24654 > 57632	2,01
19	25	24660 > 57633	1,96



CHIPBOARD STRUCTURAL, STANDARD

Topfinish

QUALIRACK LF+ TG



Structural chipboard P4 with tongue and groove for dry interior finishing such as partitions and structural flooring.

Thickness (mm)	2040x910 mm			
	#/pack	article	weight/pack	profile
19	45	400022632 > phase out	1,08	C, TG4*
22	40	400022636 > phase out	1,08	C, TG4*

Thickness (mm)	2440x610 mm			
	#/pack	article	weight/pack	profile
12	150	400051593 > 400109824	1,98	A, TG4*
18	100	400052819 > 400109870	1,93	C, TG4*

*TG4: tongue and groove all 4 edges

Topfinish

QUALIRACK SOLIDFIX LF+



Structural chipboard P4 for dry interior finishing in small format with pre-milled groove.

Thickness (mm)	595x200 mm			595x300 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
18	300	400062904 > phase out	0,47	200	400062905 > 400109996	0,47

Thickness (mm)	595x400mm			595x600 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
18	150	400062906 > phase out	0,47	100	400062907 > 400109994	0,47

Thickness (mm)	595x2400 mm		
	#/pack	article	weight/pack
18	50	400062908 > 400109995	0,93

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes






CHIPBOARD STRUCTURAL, MOISTURE RESISTANT

Topfinish

DURELIS LF+




Structural, moisture-resistant chipboard P5 for wall and floor construction.

Thickness (mm)	2500x1250 mm			2800x1196 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
10	90	24643 > 58554	2,09	90	24644 > 58555	2,24
11	80	24601 > 58557	2,04			
12	80	24724 > 58860	2,22	72	24645 > 58859	2,06 > 2,15
13				66	24646 > 58863	2,12
15	64	24604 > 58864	2,16			
18	48	24605 > 58870	1,95			
21	40	24633 > 58874	1,84			
22	40	24634 > 58875	1,93			

Thickness (mm)	3050x1250 mm			3960x1218 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
11				52	24600 > 58556	2,05
18	44	24628 > 58871	2,18			

Topfinish

DURELIS LF+



Structural, moisture-resistant chipboard P5 with low formaldehyde emission for wall and floor construction. Compliant with ChemVerbotsV

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
20	45	44684	1,95

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes



CHIPBOARD STRUCTURAL, MOISTURE RESISTANT

Topfinish

DURELIS LF+ TG



Structural, moisture-resistant chipboard P5 with tongue and groove for quick installation in wall and floor construction.

Thickness (mm)	2400x600 mm			
	#/pack	article	weight/pack	profile
18	100	400022904 > 400109957	1,87	B, TG4*
22	80	400022905 > 400109958	1,78	B, TG4*

Thickness (mm)	2440x610 mm			
	#/pack	article	weight/pack	profile
12	150	400022518 > 400109901	1,99	A, TG4*
18	100	400022519 > 400109913	1,93	C, TG4*
22	80	400022633 > 400109915	1,84	C, TG4*

Thickness (mm)	2040x910 mm			
	#/pack	article	weight/pack	profile
19	45	400022631 > 400109914	1,12	C, TG4*
22	40	400022635 > 400109917	1,15	C, TG4*
25	35	400022638 > 400109918	1,14	C, TG4*

Thickness (mm)	2440x1220 mm			
	#/pack	article	weight/pack	profile
18	50	400021846 > 400109912	1,93	C, TG2*
22	40	400022634 > 400109916	1,84	C, TG2*

*TG2: tongue and groove long edges, TG4: tongue and groove all 4 edges

Topfinish

DURELIS UNCOLOURED LF+



Structural, moisture-resistant chipboard P5 without colouring for roof construction.

Thickness (mm)	3960x1218 mm		
	#/pack	article	weight/pack
11	52	24727 > 58878	2,05

Topfinish

DURELIS PREVENT UNCOLOURED LF+



Structural, moisture-resistant chipboard P5 without colouring, with antifungal effect for roof construction.


Thickness (mm)	3960x1218 mm		
	#/pack	article	weight/pack
11	52	46617 > 59433	2,05



CHIPBOARD STRUCTURAL, MOISTURE RESISTANT

Sanded

DURELIS LF+



Structural, moisture-resistant chipboard P5 for wall and floor construction.

Thickness (mm)	2500x1250 mm			3050x1250 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
10	90	24602 > 58553	2,09			
12	80	24725 > 58861	2,22	64	24603 > 58858	2,17
16	60	24630 > 58865	2,16	50	24631 > 58866	2,20
18	50	24726 > 58873	2,03	44	24629 > 58872	2,18
22	40	24641 > 58876	1,97 > 1,93			
28				30	24642 > 58877	2,18

Lacquered on 1 side

DURELIS VAPOURBLOCK LF+



Structural, moisture-resistant chipboard P5 with airtight and vapour-retardant finish for construction applications.

Thickness (mm)	2800x1196 mm		
	#/pack	article	weight/pack
12	72	40001183 > 400109739	2,15
15	55	400045543 > 400109763	1,99

Lacquered on 1 side

DURELIS VAPOURBLOCK LF+ TG



Structural, moisture-resistant chipboard P5 with airtight and vapour-retardant finish, equipped with tongue and groove for construction applications.

Thickness (mm)	610x2440 mm			
	#/pack	article	weight/pack	profile
15	120	400054432 > 400109982	1,93	A, TG4*

*TG4: tongue and groove all 4 edges

Lacquered on 1 side

TECTO PRIME LF+



Structural, moisture-resistant chipboard P5 with white primer for roof construction.

Thickness (mm)	3960x1218 mm		
	#/pack	article	weight/pack
10	52	400045369 > 400109769	1,86

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes



CHIPBOARD STRUCTURAL, MOISTURE RESISTANT

Lacquered on 1 side

TECTO WHITE LF+




Structural, moisture-resistant chipboard P5 with white finish for roof construction.

Thickness (mm)	3960x1218 mm		
	#/pack	article	weight/pack
10	52	400094428 > 400109770	1,86

Lacquered on 2 sides

BETONFORCE BLACK



Moisture-resistant chipboard P5 for reusable formwork.

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
18	50	400011250	2,07

Melamine faced

BETONSPAN PLUS



Moisture-resistant chipboard P5 for formwork. Multiple reuse and a smooth concrete surface as result.

Thickness (mm)	2500x1250 mm		
	#/pack	article	weight/pack
18	50	131267	2,13

Sanded

SANIPAN LF+



Structural, moisture-resistant chipboard P5 pre-drilled to be used as a back wall for wall-hung toilets.

Thickness (mm)	1230x1200 mm			3034x1200 mm		
	#/pack	article	weight/pack	#/pack	article	weight/pack
18	50	41167 > 58942	0,96	44	49970 > phase out	2,02

L.MDF.H

SANIPAN MDF LF+



Structural, moisture-resistant MDF pre-drilled to be used as a back wall for wall-hung toilets.

Thickness (mm)	1200x1000 mm		
	#/pack	article	weight/pack
18	40	49971 > 60966	0,52



CHIPBOARD STRUCTURAL, MOISTURE RESISTANT & FIRE-RETARDANT

Topfinish

HYDROFLAM LF+



Flame-retardant and moisture-resistant chipboard P5 for structural construction applications, certified B-s2,d0.

Thickness (mm)	2800x1196 mm		
	#/pack	article	weight/pack
12	80	29369 > 59475	2,51

Topfinish

HYDROFLAM LF+ TG



Flame-retardant and moisture-resistant chipboard P5 with tongue and groove for structural construction applications, certified B-s2,d0.

Thickness (mm)	2400x1200 mm			
	#/pack	article	weight/pack	profile
18	50	400017194 > 400109826	1,93	B, TG2*

Thickness (mm)	2400x600 mm			
	#/pack	article	weight/pack	profile
22	80	400017341 > 400109827	1,95	B, TG4*

*TG2: tongue and groove long edges, TG4: tongue and groove all 4 edges

You see ...	This changes on 1 April 2026
article > article	current article > new REACH article
article > phase out	current article > leaves our stock range
article > new	article is new in our stock range
article	no changes



33
7075

The information provided is correct at the time of printing. For the most recent version of our stocklist, please consult our website. Contact your Unilin Panels representative for additional information.

NON-STANDARD

For non-standard panel types & sizes, we have flexible presses & high-capacity saws that support all sawing dimensions. In principle, all thicknesses and lengths / widths are possible within the press & saw capabilities.

FSC/PEFC

All articles in our stock range can be ordered with FSC or PEFC certificates.

Unilin Panels

Unilin Panels – part of the Unilin group – has been supplying innovative wood based solutions for building and interior design projects since 1960. Our chipboard, medium density fibreboard (MDF), High-Density fibreboard (HDF), High Pressure Laminate (HPL) and melamine-faced chipboards find their way to merchants in building materials and timber, industrial processors and DIY-chains worldwide.

We develop solutions tailored to your specific needs with creativity and innovation as the key drivers of our business. We continuously invest in product design and new technologies. Hence, we're recognized as a leading international player and a reliable partner in in our niche sector.

Our 1,300 employees give their all, day after day, at our production units in Belgium, France, and Germany. Altogether we produce 2.5 million m³ of panels per year.



Breestraat 2B
8710 Wielsbeke
Belgium
T +32 56 66 70 21

info.panels@unilin.com
www.unilinpanels.com



Check the current stock on My Panels:
my.unilinpanels.com. No account yet? Get in touch with your sales contact and enjoy all the benefits of our My Panels platform.



Free sample service
Scan the QR code for additional info, documents and free larger samples or visit unilinpanels.com.